

Kawasaki



# 

Venture into the great outdoors with big-bore capability on your side. Kawasaki's Brute Force® ATVs have the power to take on the toughest terrain with rugged strength and sure-footed agility. With solid construction, big muscle and cargo racks to take it all with you, Brute Force ATVs are equipped for adventure. Whether it's chores at the ranch or reaching a mountain summit, conquer the challenge with Brute Force ATVs.



Kawasaki side x sides, ATVs and Jet Ski® watercraft are assembled by Kawasaki Motors Manufacturing Corp., U.S.A. from foreign and domestic parts in Lincoln, NE.

\*Assembled in the U.S.A. badge applies to Brute Force® 750 4x4i models only



















Atomic Silver Painted Finish



Realtree Xtra® Green Camo



Timberline Green

# **BRUTE FORCE® 750 4x4i EPS**

- 749cc, V-twin, 4-stroke Engine
- Selectable 2WD/4WD Drive Modes
- Speed-sensitive Electric Power Steering (EPS)
- Independent 4-wheel Suspension
- Front and Rear Cargo Racks

# **BRUTE FORCE® 750 4x4i EPS CAMO**

- 749cc, V-twin, 4-stroke Engine
- Selectable 2WD/4WD Drive Modes
- Speed-sensitive Electric Power Steering (EPS)
- Independent 4-wheel Suspension
- · Front and Rear Cargo Racks

# BRUTE FORCE® 750 4x4i

- 749cc, V-twin, 4-stroke Engine
- Selectable 2WD/4WD Drive Modes
- Independent 4-wheel Suspension
- Front and Rear Cargo Racks













Super Black

# **BRUTE FORCE® 300**

- 271cc Liquid-cooled, 4-stroke
- Continuously Variable Transmission (CVT) with HI/LO Ranges and Reverse
- Front and Rear Cargo Racks
- 500-lb. Towing Capacity















# KFX®90

- 89cc 4-stroke Engine and Automatic Transmission
- Electric Start For Simple and Reliable Starting
- Adjustable Throttle Limiter and Continuously Variable Transmission (CVT) Collar Allows Speed and Performance to Be Adapted to Rider Experience
- Keyed Ignition Helps Prevent Unauthorized Use
- Single Shock Rear Suspension and Independent A-arm Front Suspension Contribute to Sporty Handling













Bright White

# KFX<sup>®</sup>50

- 49.5cc 4-stroke Engine and Automatic Transmission
- Electric Start For Simple and Reliable Starting
- Adjustable Throttle Limiter and Continuously Variable Transmission (CVT) Collar Allows Speed and Performance to Be Adapted to Rider Experience
- Keyed Ignition Helps Prevent Unauthorized Use
- Single Shock Rear Suspension and Independent A-arm Front Suspension Contribute to Sporty Handling

	BRUTE FORCE® 750 4x4i EPS	BRUTE FORCE® 750 4x4i	BRUTE FORCE® 750 4x4i EPS CAM
ENGINE	4-stroke, V-twin, SOHC, liquid-cooled	4-stroke, V-twin, SOHC, liquid-cooled	4-stroke, V-twin, SOHC, liquid-cooled
DISPLACEMENT	749cc	749cc	749cc
BORE X STROKE	85.0 x 66.0mm	85.0 x 66.0mm	85.0 x 66.0mm
COMPRESSION RATIO	9.3:1	9.3:1	9.3:1
MAXIMUM TORQUE	42.7 lb-ft @ 4750 rpm	42.7 lb-ft @ 4750 rpm	42.7 lb-ft @ 4750 rpm
FUEL SYSTEM	DFI® with two 36mm throttle bodies	DFI® with two 36mm throttle bodies	DFI® with two 36mm throttle bodies
IGNITION	Digital DC-CDI	Digital DC-CDI	Digital DC-CDI
TRANSMISSION	Automatic CVT (H,L,N,R)	Automatic CVT (H,L,N,R)	Automatic CVT (H,L,N,R)
FINAL DRIVE	Selectable 2WD/4WD with variable control front differential lock, shaft	Selectable 2WD/4WD with variable control front differential lock, shaft	Selectable 2WD/4WD with variable control front differential lock, shaft
FRONT SUSPENSION / WHEEL TRAVEL	Double wishbone/6.7 in	Double wishbone/6.7 in	Double wishbone/6.7 in
REAR SUSPENSION / WHEEL TRAVEL	Double wishbone/7.5 in	Double wishbone/7.5 in	Double wishbone/7.5 in
FRONT TIRE	AT 25 x 8-12	AT 25 x 8-12	AT 25 x 8-12
REAR TIRE	AT 25 x 10-12	AT 25 x 10-12	AT 25 x 10-12
FRONT BRAKES	Dual hydraulic 176mm discs with 2-piston calipers	Dual hydraulic 200mm discs with 2-piston calipers	Dual hydraulic 200mm discs with 2-piston calipers
REAR BRAKES	Sealed, oil-bathed, multi-disc with independent park brake	Sealed, oil-bathed, multi-disc with independent park brake	Sealed, oil-bathed, multi-disc with independent park brake
GROUND CLEARANCE	9.4 in	9.4 in	9.4 in
STARTING SYSTEM	Electric	Electric	Electric
FUEL CAPACITY	5.0 gal	5.0 gal	5.0 gal
ELECTRONIC POWER STEERING (EPS)	Yes	No	Yes
TURNING RADIUS	10.5 ft	10.5 ft	10.5 ft
TOWING CAPACITY	1250 lb	1250 lb	1250 lb
TOTAL RACK CAPACITY	242.0 lb	242.0 lb	242.0 lb
RACK CAPACITY, FRONT/ REAR	88.0/176.0 lb	88.0/176.0 lb	88.0/176.0 lb
LIGHTING	35W headlights, 5W taillight, 21W stoplight	35W headlights, 5W taillight, 21W stoplight	35W headlights, 5W taillight, 21W stoplight
FRAME TYPE	Double-cradle, high-tensile tubular steel	Double-cradle, high-tensile tubular steel	Double-cradle, high-tensile tubular steel
TRACK FRONT/REAR	36.4/35.0 in	36.4/35.0 in	36.4/35.0 in
OVERALL LENGTH	86.4 in	86.4 in	86.4 in
OVERALL WIDTH	46.5 in	46.5 in	46.5 in
OVERALL HEIGHT	48.0 in	48.0 in	48.0 in
SEAT HEIGHT	35.8 in	35.8 in	35.8 in
CURB WEIGHT	699.0 lb**	688.0 lb**	699.0 lb**
WHEELBASE	50.6 in	50.6 in	50.6 in
INSTRUMENTS	Speedometer, odometer, dual trip meters, fuel gauge, engine temp, clock, hour meter and 2WD/4WD icon, plus indicators for EPS, neutral, belt, and oil pressure	Speedometer, odometer, dual trip meters, fuel gauge, engine temp, clock, hour meter and 2WD/4WD icon, plus indicators for neutral, reverse, belt, and oil pressure	Speedometer, odometer, dual trip meters, fuel gauge, engine temp, clock, hour meter and 2WD/4WD icon, plus indicators for EPS neutral, belt, and oil pressure
COLOR CHOICES	Atomic Silver, Bright White, Vibrant Blue	Timberline Green	Realtree Xtra® Green Camo
WARRANTY	12 Month Limited Warranty	12 Month Limited Warranty	12 Month Limited Warranty
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24, 36, or 48 months	12, 24, 36, or 48 months	12, 24, 36, or 48 months

<sup>\*\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). Specifications subject to change.

	2018 BRUTE FORCE® 300	
ENGINE	4-stroke, 1-cylinder, SOHC	
DISPLACEMENT	271cc	
BORE X STROKE	72.7 x 65.2mm	
COMPRESSION RATIO	11.0:1	
MAXIMUM TORQUE	15.9 lb-ft @ 6500 rpm	
FUEL SYSTEM	Keihin CVK32 carburetor	
IGNITION	DC-CDI	
TRANSMISSION	Automatic CVT with centrifugal clutch (H,L,N,R)	
FINAL DRIVE	2WD, Shaft	
FRONT SUSPENSION / WHEEL TRAVEL	Independent double wishbone/5.2 in	
REAR SUSPENSION / WHEEL TRAVEL	Swingarm/5.6 in	
FRONT TIRE	AT 22 x 7-10 Maxxis tubeless	
REAR TIRE	AT 22 x 10-10 Maxxis tubeless	
FRONT BRAKES	Dual 180mm discs	
REAR BRAKES	Single 180mm disc	
GROUND CLEARANCE	6.1 in	
STARTING SYSTEM	Electric	
FUEL CAPACITY	3.2 gal	
ELECTRONIC POWER STEERING (EPS)	No	
TURNING RADIUS	9.2 ft	
TOWING CAPACITY	500 lb	
TOTAL RACK CAPACITY	110 lb	
RACK CAPACITY, FRONT/REAR	44/66 lb	
LIGHTING	(2) 35W headlights, 5W taillight and 21W stoplight	
FRAME TYPE	Double cradle, steel	
TRACK FRONT/REAR	33.5/32.7 in	
OVERALL LENGTH	75.4 in	
OVERALL WIDTH	42.5 in	
OVERALL HEIGHT	46.1 in	
SEAT HEIGHT	33.3 in	
CURB WEIGHT	535.8 lb**	
WHEELBASE	45.9 in	
INSTRUMENTS	Speedometer, odometer, clock, fuel gauge and coolant temp light	
COLOR CHOICES	Super Black, Bright White	
WARRANTY	12 Month Limited Warranty	
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24, 36, or 48 months	

<sup>\*\*\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

Specifications subject to change.



	KFX®90	KFX®50
ENGINE	4-stroke, forced-air cooled, single	4-stroke, air-cooled, single
DISPLACEMENT	89.0cc	49.5cc
BORE X STROKE	47.0 x 51.8mm	39 x 41.4mm
COMPRESSION RATIO	10.0:1	10.0:1
MAXIMUM TORQUE	N/A	N/A
FUEL SYSTEM	Mikuni PTE 16	Keihin PTE 16
IGNITION	Solid state CDI	Solid state CDI
TRANSMISSION	Automatic CVT	Automatic CVT
FINAL DRIVE	2WD, Chain	2WD, Chain
FRONT SUSPENSION / WHEEL TRAVEL	Single A-arm/2.8 in	Single A-arm/2.8 in
REAR SUSPENSION / WHEEL TRAVEL	Swingarm/2.9 in	Swingarm/2.9 in
FRONT TIRE	AT 18 x 7-8 tubeless	AT 16 x 8-7 tubeless
REAR TIRE	AT 18 x 9-8 tubeless	AT 16 x 8-7 tubeless
FRONT BRAKES	Dual mechanical drums	Dual mechanical drums
REAR BRAKES	Hydraulic disc	Hydraulic disc
GROUND CLEARANCE	At rear axle - 3.9 in	At rear axle - 3.3 in
STARTING SYSTEM	Electric with back-up kick-starter	Electric with back-up kick-starter
FUEL CAPACITY	1.5 gal	1.5 gal
ELECTRONIC POWER STEERING (EPS)	No	No
TURNING RADIUS	8.7 ft	8.7 ft
TOWING CAPACITY	N/A	N/A
TOTAL RACK CAPACITY	N/A	N/A
RACK CAPACITY, FRONT/REAR	N/A	N/A
LIGHTING	N/A	N/A
FRAME TYPE	Double cradle, steel	Double cradle, steel
TRACK FRONT/REAR	26.8/26.0 in	27.2/27.6 in
OVERALL LENGTH	56.1 in	55.1 in
OVERALL WIDTH	35.6 in	34.7 in
OVERALL HEIGHT	36.4 in	35.8 in
SEAT HEIGHT	25.6 in	25.0 in
CURB WEIGHT	266.8 lb**	245.0 lb**
WHEELBASE	38.0 in	38.0 in
INSTRUMENTS	N/A	N/A
COLOR CHOICES	Lime Green, Bright White	Lime Green, Bright White
WARRANTY	12 Month Limited Warranty	12 Month Limited Warranty
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24, 36, or 48 months	12, 24, 36, or 48 months

<sup>\*\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

Specifications subject to change.







### Zedmotorz

Surra 45703, Kuwait,

**PHONE:** +96524828072 **FAX:** +96524828073

**EMAIL:** zed@zedmotorz.com **WEBSITE:** www.zedmotorz.com

### **LIMITED WARRANTY**

Your new Kawasaki ATV comes with a 12-month limited warranty.

# **UP TO FOUR YEARS ADDITIONAL COVERAGE**

Let Kawasaki protect your new ATV for years to come with Kawasaki Protection Plus™. This plan repairs or replaces covered components free of charge if found defective in material or workmanship. Everything about the plan is easy. There's no deductible. It's honored at every authorized Kawasaki dealer nationwide. It's transferable to another owner with no fee. Just ask your dealer how you can buy additional coverage of 12, 24, 36 or 48 months, depending on the model and plan purchased. FL Lic #65500, Kawasaki Motors Corp., U.S.A., PO Box 25252, Santa Ana, CA 92799, (949) 770-0400.

### **KAWASAKI CARES**

Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki's KFX\*50 is recommended for use only by persons 6 or older, and the KFX\*90 is recommended for use only by persons 12 and older. All children under 16 riding ATVs should always have direct adult supervision. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1 (800) 887-2887, or go to www.atvsafety.org. ©2018 Kawasaki Motors Corp., U.S.A.



Kawasaki subscribes to the guidelines of Tread Lightly!\* a program dedicated to protecting the great outdoors through education and fostering responsible enjoyment of public lands.



\*Assembled in the U.S.A. badge applies to Brute Force\* 750 4x4i models only.



All trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Accessorized unit shown.

Printed in U.S.A. 99969-3727

